


DESCO INDUSTRIES INC. Technical Bulletin TB-7033

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200, Standard must be consulted for specific requirements.

NFPA Designation 704

Degree of Hazard:
4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant



IDENTITY (As Used on Label and List)

Wescorp Antistatic Cellulose Tape

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Desco Industries Inc.	Emergency Telephone Number (909) 627-8178
Address (Number, Street, City, State, and Zip Code) 3651 Walnut Avenue, Chino, CA 91710	Telephone Number for Information (909) 627-8178
	Date Prepared 2-1-2006
	Signature of Preparer (Optional)

Section II - Physical/Chemical Characteristics

Solubility in Water Negligible
Volatility at 100°C Less than 0.1%

Section III - Hazardous Ingredients

Hazardous Ingredients None

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL	UEL
Extinguishing Media Water, dry chemicals, foam, and CO ₂			
Unusual Fire and Explosion Hazards Produces dense black smoke if burned			

Section V - Reactivity Data

Reactivity Not Reactive	Conditions to Avoid Exposure to temperatures in excess of 200°C/392°F cause decomposition.
----------------------------	---

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? None Known	Skin? Minor Irritation	Ingestion? None Known
Health Hazards (Acute and Chronic): None known			
Signs and Symptoms of Exposure Skin: May cause skin irritation after prolonged exposure with adhesive side to skin.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken In Case Material is Released or Spilled N/A
--

Section VII - Spill or Leak Procedures

N/A

Section VIII - Special Protection Information

N/A

N/A = Not Applicable; NE = None Established