STATSHIELD® METAL-OUT SERIES

Specifications:

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/ESD S11.4

Electrical Properties Typical Values Surface Resistance:

Outer Surface $1 \times 10^4 \text{ to} < 1 \times 10^8 \text{ ohms}$ Inner Surface $1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$ Discharge Shielding <20 nJ Charge Generation

Capacitance Probe (to dissipate 1 KV) <30 volts

ANSI/ESD STM11.11 ANSI/FSD STM11 11 ANSI/ESD STM11.31. EIA 541 Teflon: -0.03 nC/sq. in. Modified Incline Plane

Quartz: +0.10 nC/sq. in. Modified Incline Plane

ANSI/EIA-541/Appendix E. 1kV Discharge

Meets Requirements of:

ESD Protective Packaging

Test Procedures/Method

MIL-STD-3010, 1003

MIL-STD-3010, 2065

375°F, 1/2 sec 60 psi

MIL-STD-3010. M3005

ASTM D-1003

Level 3 Technical Requirements

Physical Properties:

Film Thickness Width (Inside Dimensions) Nominal -0" / + 0.125" Length (Inside Dimensions) Nominal ± 0.125" Light Transmission 40% (Tobias) Date & Lot Code Puncture Resistance >10 lbs Heat Seal >10 lbs/in. Non-corrosive Pass

FTIR IPC-TM-650 2.4.1


Nominal 0.003" (0.0762mm) ±10% Silicone Not detected Marking Adhesion Pass

Soft Fold Bottom

Printed for QC

Traceablility

Weld



Width (W)

Side Weld Seals 3/8 in. (±0.10)

Opening

Length (L)

Weld

Seal

STATSHIELD®

RoHS

Static Shielding Ba

DescoIndustries.com

Made in America

Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7507.

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS. REACH and Conflict Minerals Statement

See the Desco Industries RoHS. REACH, and Conflict Minerals Statement: Desco.com/pdf/REACHRoHSConflictMinerals-Desco Bags.pdf

See the Desco Limited Warranty:

Desco.DescoIndustries.com/Limited-Warranty.aspx

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE



Specifications and procedures subject to change without notice.

STATSHIELD® BAG, SHIELDING, METAL-OUT CONSTRUCTION, 0.003" (0.0762mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 13010

DATE: April 2018